## NATIONAL UNIVERSITY OF SCIENCE AND TECHNOLOGY

## FACULTY OF INDUSTRIAL TECHNOLOGY BACHELOR OF ENGINEERING (HONS) DEGREE Part One Examination February 2010

## **TCE1101 Chemical Engineering Calculations**

**Duration of Examination 3 Hours** 

## Instructions to Candidates:

- 1. Answer ALL FIVE questions.
- 2. Each question carries equal marks.
- 3. Show all your steps clearly in your calculation.
- 4. Start the answers for each question on a new page.
- **1.** a) Phosphoric acid is a colorless deliquescent acid used in the manufacture of fertilizers and as a flavoring agent in drinks. For a given 10 wt % phosphoric acid solution of specific gravity 1.10 determine:
  - a. the mol fraction composition of this mixture.
  - b. the volume (in US gallons) of this solution which would contain 1 g mol H3PO4. (MW  $H_3PO_4 = 97.97$ ) (8 marks)
  - **b)** A U-tube manometer is used to determine the pressure drop across an orifice meter. The liquid flowing in the pipe line is a sulfuric acid solution having a specific gravity  $(60^{\circ}/60^{\circ})$  of 1.250. The manometer liquid is mercury, with a specific gravity  $(60^{\circ}/60^{\circ})$  of 13.56. The manometer reading is 5.35 inches, and all parts of the system are at a temperature of  $60^{\circ}F$ .

What is the pressure drop across the orifice meter in psi. (12 marks)

2. TiCl4 can be formed by reacting titanium dioxide (TiO2) with hydrochloric acid. TiO2 is available as an ore containing 78 % TiO2 and 22 % inerts. The HCl is available as 45 wt% solution (the balance is water). The per pass conversion of TiO2 is 75 %. The HCl is fed into the reactor in 20 % excess based on the reaction. Pure unreacted TiO2 is recycled back to mix with the TiO2 feed.

For 1 kg of TiCl4 produced, determine:

- a) the kg of TiO2 ore fed.
- **b)** the kg of 45 wt % HCl solution fed.
- c) the ratio of recycle stream to fresh TiO2 ore (in kg).

**(20 marks)** 

- 3. a) A gas analyzes 60% methane and 40% ethylene by volume. It is desired to store 12.3 kg of this gas mixture in a cylinder having a capacity of  $5.14 \times 10^{-2}$  m3 at a maximum temperature of  $45^{\circ}$ C. Calculate the pressure inside the cylinder by:
  - (i) assuming that the mixture obeys the ideal gas laws;
  - (ii) using the compressibility factor determined by the pseudo critical point method.

(15 marks)

**b)** A cylinder 0.150m<sup>3</sup> in volume containing 22.7 kg of propane C<sub>3</sub>H<sub>8</sub> stands in the sun. A gauge pressure shows that the pressure is 4790 kPa gauge. What is the temperature of the propane in the cylinder. Use van der Waal's equation of state.

Take: 
$$a = 9.24 \times 10^6 atm \left(\frac{cm^3}{gmol}\right)^2$$
,  $b = 90.7 \left(\frac{cm^3}{gmol}\right)$  (5 marks)

- **4. a)** A steel tank having a capacity of 25 m³ holds carbon dioxide at 30°C and 1.6 atm. Calculate the weight, in grams, of the carbon dioxide. (7 marks)
  - **b)** A stream of hot water at 150 °F flowing at a rate of 50 US gal/min is to be produced by mixing water at 60 °F and steam at 30 psia and 280 °F in a suitable mixer. What are the required flow rates of steam and cold water. Assume Q = 0.

Take: Steam 30 psia, 280° F, 
$$\Delta \hat{H} = 1179 Btu/lb$$
  
Water 150°F  $\Delta \hat{H} = 117.87 Btu/lb$ , water 60°F  $\Delta \hat{H} = 28.07 Btu/lb$  (13 marks)

5. Argon gas in an insulated plasma deposition chamber with a volume of 2 L is to be heated by an electric resistance heater. Initially, the gas, which can be treated as an ideal gas, is at 1.5 Pa and 300 K. The 1000-ohm heater draws current at 40V for 5 minutes (i.e., 480 J of work is done on the system by its surroundings). What is the final gas temperature and pressure in the chamber? The mass of the heater is 12 g and its heat capacity is 0.35 J/gK. Assume that the heat transfer through the walls of the chamber from the gas at this low pressure and in the short time period can be considered negligible.

Take:  $C_{V,ideal gas} = 3/2R$ ,  $C_V = C_P - R$ ,  $C_P = 5/2R$  (20 marks)



