

**NATIONAL UNIVERSITY OF SCIENCE AND TECHNOLOGY
DEPARTMENT OF CIVIL AND WATER ENGINEERING
FACULTY OF INDUSTRIAL TECHNOLOGY
BACHELOR OF ENGINEERING (HONOURS) DEGREE
PART V FIRST SEMESTER EXAM.- APRIL 2009
WATER QUALITY MANAGEMENT: TCW 5201**

INSTRUCTIONS

Answer any four questions.

Time: 3 hours
Total Marks: 100

QUESTION 1

- (a) Define the following terms of disease transmission related to water and give at least two examples of diseases that fall under each category: (i) water borne, (ii) water washed, (iii) water based and (iv) water related insect vector. (13 marks)
- (b) A discrete spherical particle has a diameter of 0.15mm and a relative density of 1.2. Calculate the settling velocity in water at 20°C. (Kinetic viscosity of water at 20°C is $1.01 \times 10^{-6} \text{ m}^2/\text{s}$). (12 marks)

QUESTION 2

- (a) Describe any five factors that influence the bactericidal efficiency of chlorine in water. (11marks).
- (b) A Stream with a flow of $0.75 \text{ m}^3/\text{sec}$ and BOD 3.3 mg/L is saturated with DO (9.17 mg/L at 20°C). It receives an effluent discharge of $0.25 \text{ m}^3/\text{sec}$, BOD 20 mg/L and DO 5.0 mg/L . Determine the DO deficit at a point 35 km down stream if the average velocity of flow is 0.2 m/sec. Assume temperature is 20°C throughout, K_1 for effluent / water mixture is 0.10/day, K_2 for stream is 0.40/day. (14 marks)

QUESTION 3

- (a) Compare slow sand filters with rapid sand filters. (12marks)
- (b) A filter bed is made of 0.45 mm size angular sand ($\theta = 0.73$) and has an overall depth of 800mm and a porosity of 40 percent. Use Corman-Kozeny formular to estimate the head loss of the clean bed at a filtration rate of $120 \text{ m}^3/\text{m}^2 \text{ day}$. Kinetic viscosity of water = $1.01 \times 10^{-6} \text{ m}^2/\text{s}$. (13marks)

QUESTION 4

- (a) Describe the purpose of carrying out a jar Test in water treatment and explain the procedures involved in doing it. (10 marks)
- (b) A filter sand bed of depth 0.8m and porosity 0.44 is backwashed at $1.5 \times 10^3 \text{ m}^2/\text{m}^2$ (kinematic viscosity of water = $1.2 \times 10^{-6} \text{ m}^2/\text{s}$). If the sand grains are of 0.8mm diameter and density of $2650 \text{ kg}/\text{m}^3$, calculate the height of the expanded bed, and its porosity after it is fluidified. (15 marks)

QUESTION 5

- (a) Describe the compounds that are formed when chlorine is added to:
- (i) Water free from organic matter and ammonia. (5marks)
 - (ii) Water in which ammonia is present. (5marks)
 - (iii) Which of the compounds formed in the chemical reactions above are most effective or powerful bactericides. (5 marks)
- (b) Calculate the contact time (in minutes) required to reduce the number of E-coli bacteria by 99.4% from a wastewater in which residual chlorides level is $2 \text{ mg}/\text{l}$. (10marks)

USEFUL FORMULAE

$$V_s = \frac{g(\rho_p - \rho_w)d^2}{18\mu}$$

$$V_s = \sqrt{\frac{4gd(\rho_p - \rho_w)}{3C_d}}$$

$$C_d = \frac{18.5}{Re^{0.6}}$$

$$C = \frac{24}{Re} + \frac{3}{\sqrt{Re}} + 0.34$$

$$Re = \frac{\phi V_s \rho d}{\mu}$$

$$V_s = \sqrt{\frac{4gd(\rho_p - \rho_w)}{3C_d}}$$

$$t_c = \frac{1}{K_2 - K_1} \log \frac{K_2}{K_1} \left[\frac{1 - \frac{D_o(k_2 - k_1)}{L_o K_1}}{1} \right]$$

$$D_c = \frac{K_1}{K_2} L_o - K_1 - K_1 t_c$$

$$D_t = \frac{K_1}{K_2 - K_1} L_o (10^{-K_1 t} - 10^{-K_2 t}) + D_o 10^{-K_2 t}$$

$$\log_{10} \left(\frac{N_t}{N_o} \right) = K t^2$$

$$h = \frac{1.07 \frac{L_o V^2}{4}}{\phi g d f}$$

Particles shape factor, ϕ for spherical sand = 1.0, worn sand = 0.7 and angular sand = 0.73

$$\frac{h}{1} = \frac{(1-f)}{f^3} \frac{V_s^2}{g d \phi}$$

$$E = 150$$

