NATIONAL UNIVERSITY OF SCIENCE AND TECHNOLOGY DEPARTMENT OF CIVIL AND WATER ENGINEERING FACULTY OF INDUSTRIAL TECHNOLOGY BACHELOR OF ENGINEERING (HONOURS) DEGREE PART V FIRST SEMESTER EXAMINATION- DECEMBER 2006 DESIGN OF STRUCTURES II – TCW 5102

INSTRUCTIONS

Answer All Questions Open Book Examination

Time: 4hours Total Marks:100

QUESTION ONE

Analyse the continuous beam for the three load cases shown in Figure 1.0. Draw the separate shear force and bending moment diagram for ultimate loads. Construct the maximum shear force and bending moment envelopes.

Assume characteristic dead load $g_k = 20.0 \text{ kN/m};$ TL - Total Load characteristic imposed load $q_k = 10.0 \text{ kN/m}$ DL - Dead Load **Case 1.0** TLTLTL**Case 2.0** TL DL DL **Case 3.0** TL DL TL8000 6000 8000

Figure 1.0

Marks 30

QUESTION TWO

Design the end span of the continuous beam analysed in Question One. The materials are grade 30 concrete and grade 460 and 250 reinforcement. Assume cover to reinforcement as 30 mm

Marks 20

QUESTION THREE

Design a single angle tie to carry a characteristic dead load of 80kN and a characteristic imposed load of 35 kN and connected by

- (a) welded connection connected by long leg
- (b) bolted connection connected by long leg

Material: Use Grade 43 steel

Marks25

QUESTION FOUR

(a) Design an angle purlin for a roof with slope of 1 in 2.5. The purlins are simply supported and span 5.0m between roof trusses. The purlins are at 1.6m centers. The characteristic dead load, including self weight of purlin, is 0.35 kN/m 2 on the slope and the characteristic imposed load is 0.75 kN/m 2 on plan. Use Grade 43 steel.

Marks 15

(b)Design the purlin using the empirical method from BS 5950

Marks 10



