

NATIONAL UNIVERSITY OF SCIENCE AND TECHNOLOGY

Faculty of Industrial Technology

Department of Technical Teacher Education

Manufacturing Technology -TBE1246

September 2010 Examination

Instructions

1. Examination length is **3hrs**.
2. Each question carries twenty (**25**) marks and there are five (**5**) questions in total.
3. Attempt any four questions.

Question 1

Non-ferrous water taps are sand cast. Describe using illustrations where necessary the steps that are followed in the mass production of these components. **[25]**

Question 2

- a) Explain the role of the surface area of a casting during solidification. **[5]**
- b) With the aid of Chvorinov's rule calculate the relative solidification times for castings of unity volume and of the following shapes, cast in ceramic moulds:
 - i. Sphere of diameter d **[3]**
 - ii. Cylinder with $h/d = 1$ **[3]**
 - iii. Cylinder with $h/d = 10$ **[3]**
 - iv. Cube of width $2d$ **[3]**
- c) Plot the results in 2b on graph paper to illustrate the effect of shape changes. Comment on the graph obtained. **[8]**

Question 3

- a) Discuss the forms of shrinkage that occur during casting and how, if possible, they can be countered. **[10]**

- b) The nature of the casting operation presents numerous opportunities for defects to appear in the product. Give and explain any five defect categories. [15]

Question 4

- a) State the furnace types commonly found in foundries. [4]
b) Discuss the considerations in choosing a furnace. [12]
c) Describe plaster moulding. [9]

Question 5

A steel plate casting 5 cm x 7 cm x 35 cm is poured in 20 seconds, the effective sprue height is 15 cm, and the gating ratio is 1:3:1.5. The density of steel is 7.86 g/cm³ and the casting yield is 74%. The cylindrical tapered sprue is connected to two square runners, and each runner is connected to two gates that have a width two times the height. The dynamic viscosity of steel is 0.06 g/cm.sec. Determine the following:

- a) The amount of metal poured (g and cm³). [4]
b) The pouring rate (g/s and cm³/s). [3]
c) The choke velocity (cm/s). [2]
d) The choke area and the location of the choke. [4]
e) The dimensions of the sprue base, each runner, and each gate (cm). [8]
f) The Reynolds number for melt flow in the runners. Comment on the nature of melt flow in the runners. [4]

End of exam

**NATIONAL UNIVERSITY OF SCIENCE AND TECHNOLOGY
DEPARTMENT OF TECHNICAL TEACHER EDUCATION
SUPPLEMENTARY EXAMINATIONS: 2010
TBE 1290 – PREPERATION
TIME: 3 HOURS**

INSTRUCTIONS

Instructions to candidates

Answer ALL questions.

QUESTION 1

- (a) Explain why acid dyes are classified as anionic and why they combine directly with animal fibres but not with vegetable fibres. **4marks**
- (b) Discuss the application classification of acid dyes. Comment on the relative fastness properties of these classes. **12marks**
- (c) Most direct dyes have limited wet fastness in medium to full shades unless they are after-treated. List four (4) methods of improving fastness properties of direct dyes. **4 marks**

QUESTION 2

- (a) State and explain the main stages in the dyeing of cellulosic fabrics with vat dyes. Comment on the fastness properties of this class of dyes. **6marks**
- (b) Suggest with reasons the end use application of sulphur dyes. **4marks**
- (c) What is the role of desizing on cotton fabrics? How is desizing carried out on cotton? **4marks**
- (d) Explain the aims and objectives of fabric preparation. **6marks**

QUESTION 3

- (a) With aid of illustrations/diagrams explain why reactive dyes have wet fastness properties. **4marks**
- (b) When dyeing with reactive dyes, fast addition of alkali may cause fast strike. Explain why. What problem/s can this cause? **2 marks**
- (c) Why do reactive dyes have a relatively large number of sulphonic acid groups? **2marks**
- (d) Outline the fastness properties of reactive indicating what end uses would products dyed with these dyes be used for. **6marks**
- (e) Why is it essential to use retarders when dyeing acrylics with basic dyes? Give examples of one common retarder. **3marks**

(f) Given the following: Weight of fabric to dyed 1000kg

Liquor ratio 10:1

Salt 50g/l

Depth of shade of blue direct dye 2% owf

Calculate

- i. amount dye required
- ii. amount of salt
- iii. amount of liquor

3marks

QUESTION 4

(a) Define printing? 2marks

(b) What do you understand by the following terms used in printing:

- i. Batik
- ii. Design repeat
- iii. Squeegee
- iv. Binder
- v. Water retaining agent
- vi. Cross-linking agent

6marks

(c) Explain the printing procedure adopted when printing with pigments. 6marks

(d) Give reasons why pigment accounts for more than fifty percent of all printing worldwide. **6marks**

QUESTION 6

(a) Discuss the procedures for printing of cellulose using reactive dyes. **10marks**

(b) Compare and contrast the flat bed printing machine and rotary screen printing machine. **10marks**

END OF EXAMINATION PAPER